



## Differential Pressure Switch

with adjustable switching pressure for HVAC-Applications



measuring  
•  
monitoring  
•  
analysing

### SCH-PSB



- Setting range:  
20 ... 300 Pa up to  
200 ... 1000 Pa
- $p_{\max}$ : 10 kPa
- $t_{\max}$ : +70 °C
- Connection: hose ports



P3

KOBOLD companies worldwide:

ARGENTINA, AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLOMBIA, CZECHIA, EGYPT, FRANCE, GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, ROMANIA, SINGAPORE, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, TURKEY, USA, VIETNAM

KOBOLD Messring GmbH  
Nordring 22-24  
D-65719 Hofheim/Ts.  
Head Office:  
+49(0)6192 299-0  
+49(0)6192 23398  
info.de@kobold.com  
www.kobold.com

### Applications

Adjustable differential pressure switch for monitoring over-pressure, vacuum and differential pressure of air or other non-combustible, non-aggressive gases. Possible fields of application include:

- Monitoring air filters and ventilators
- Monitoring industrial cooling-air circuits
- Overheating protection for fan heaters
- Monitoring flows in ventilation ducts
- Controlling air and fire-protection flaps
- Frost protection for heat exchangers

### Versions

With this pressure switch the switching pressure can be adjusted without a pressure gauge using a scaled adjustment knob. The switching differential can also be adjusted with a screwdriver.

Model	Adjustment range for upper switching pressure [Pascal]	Switching differential set to [Pascal]	Tolerance for upper and lower switching pressure
SCH-PSB-0300	20 ... 300	10	±15%
SCH-PSB-0500	50 ... 500	20	±15%
SCH-PSB-1000	200 ... 1000	100	±15%

Switching pressure specifications apply to vertical installation which is also the recommended position with pressure-pipe connections pointing downwards. If the switches are installed horizontally with AMP connection terminals uppermost, the switching values are approximately 20 Pa higher.

### Technical Details

Maximum operating pressure: 10 kPa for all pressure ranges  
 Medium: air, non-combustible and non-aggressive gases

### Temperature range


Medium and ambient temperature: -20 °C ... +70 °C (limited from +85 °C to +70 °C due to PVC-hose)  
 Storage temperature: -40 °C ... +70 °C (limited from +85 °C to +70 °C due to PVC-hose)

Diaphragm material: silicone, tempered at 200 °C ge-tempert, free of gas emissions

Pressure connections: 2 plastic pipe connection pieces (P1 and P2), external diameter 6.0 mm:  
 P1 for connection to higher pressure (marked +);  
 P2 for connection to lower pressure (marked -)

### Housing materials

Switch body: PA 6.6

Cover: PS  
 Weight: 150 g  
 Mechanical working life: over 10<sup>6</sup> switching operations.  
 Electrical rating: max. 1.0 A (0.4 A) / 250 V<sub>AC</sub>  
 Electrical connections: AMP flat plug 6.3x0.8 mm acc. to DIN 46244 or push-on screw terminals. Cable conduit with cable strain relief.  
 Cable entry: M16x1.5  
 Mounting: with fastening lugs  
 Arrangement of contacts:  1 Break contact  
 2 Operating contact  
 3 Power supply line  
 Protection: IP 54

### Order Details (Example: SCH-PSB-0300)

Model	Pressure ranges [Pascal]
SCH-PSB-...	... 0300 = 20 ... 300
SCH-PSB-...	... 0500 = 50 ... 500
SCH-PSB-...	... 1000 = 200 ... 1000

### Accessories included in scope of delivery

2 m PVC hose and 2 plastic tubes made of ABS  
 Set consisting of three push-on screw terminals

### Dimensions [mm]

