## Request for Quotation- PA Series Products SD / SRD / D-Stop / D-Lock

☐SD (Declutchable Manual Override) ☐ SRD (Non-Declutching Manual Override) ☐ D-Stop (Partial Stroke Testing Device) ☐D-Lock (Zero Degree Lockout)	
Application: Please provide a brief description of type of service including line media and application temperature requirements.	
Actuator Information: Manufacturer	Model
☐Pneumatic ☐Electric ☐Hydraulic	☐Double Acting ☐Spring Return
☐Fail CW ☐Fail CCW Torque: ☐Inch Lbs. ☐Ft Lbs. ☐NM PSI	
DA Max Output Tq Spring Start Tq Spring End Tq	
Mounting Information: Tap Size Qty of holes BCD On Centerline	
Output Drive Information: Drive Type and Size  Standard Blank Drive Coupling	
☐ Drawing Enclosed	
Note: Typically information on actuators is more readily available than information on valves. If mounting and drive information is not available, please make sure to supply actuator manufacturers name and model number as a minimum requirement for quotation.	
Valve Information: Manufacturer	Model Size
Type: ☐BFV ☐HPBFV ☐Plug ☐Ball ☐Damper Torque: ☐Inch Lbs.☐Ft Lbs. ☐NM	
Seating Torque Unseating Torque	
Valve Stem Type: Shaft w/Key Flatted Square Other	
Packing Gland:	
Mounting Information: Mounting information varies widely from manufacture to manufacture. If DynaTorque is to be responsible for PA series to valve interface, DynaTorque requires valve top works drawings to be part of the request for quotation information package.	
D-Stop Only: Rotation: ☐Standard 20 Degree (Toward Fail Position) ☐Special Rotation Requirement	
☐Namur Switch Bracket ☐Automated Engagement ☐Unique Engagement Keys	