



Series HPP60-450 DN20-22 PN315




HPP 60-150

1) Connection for the potential equalization, only for application in the explosive area.



HPP 170-450



Dimensions:

type	HPP 60	HPP 90	HPP 150	HPP 170	HPP 240	HPP 360	HPP 450
connection	DN 20			DN 22			
A	202	267	376	285	335	415	522
B	80	80	80	95			
C	270	335	445	350	400	480	585
D	20			22			
E	28			30			
F	65			90			
weight	5 kg	5,5 kg	6,5 kg	15 kg	16 kg	18 kg	20 kg
volume tank	0,3 l	0,4 l	0,6 l	0,7 l	0,9 l	1,2 l	1,6 l

Dimensions: mm

Designs and performance values are subject to change.



Powering Business Worldwide

Pressure Filter

Series HPP60-450

DN20-22 PN315

Description:

Pressure filter series HPP60-450 have a working pressure up to 315 bar. Pressure peaks can be absorbed with a sufficient safety margin. The HPP-filter are flanged to the mounting surface.

The filter element consists of star-shaped, pleated filter material, which is supported on the inside by a perforated core tube and is bonded to the end caps with a high-quality adhesive. The flow direction is from outside to inside. Filter elements are available down to $5 \mu\text{m}_{(c)}$. Finer filtration is available upon request.

For cleaning the stainless steel mesh element (see special leaflets 21070-4 and 39448-4) or changing the filter element, remove the filter bowl and take out the element. The mesh elements are not guaranteed to maintain 100% performance after cleaning.

Eaton filter elements are known for high intrinsic stability and an excellent filtration capability, a high dirt-retaining capacity and a long service life.

Eaton filter can be used for petroleum-based fluids, HW emulsions, water glycols, most synthetic fluids and lubrication fluids. Consult factory for specific fluid applications.

Eaton filter elements are available up to a pressure resistance of Δp 160 bar and a rupture strength of Δp 250 bar.

The internal valves are integrated into the centering pivot for the filter element. After reaching the opening pressure the by-pass valve causes that an unfiltered partial flow passes the filter.

With the reverse valve a protection of the filter element is given when having a reverse flow inside the filter. The reverse flow will not be filtered.

Type index:

Complete filter: (ordering example)

HPP. 90. 10VG. HR. E. P. -. P. 4. -. -. AE

1	2	3	4	5	6	7	8	9	10	11	12
---	---	---	---	---	---	---	---	---	----	----	----

- 1 series:**
HPP = pressure filter, manifold mounted
- 2 nominal size:** 60, 90, 150, 170, 240, 360, 450
- 3 filter-material:**
80G, 40G, 25G stainless steel wire mesh
25VG, 16VG, 10VG, 6VG, 3VG, 1VG microglass
- 4 filter element collapse rating:**
30 = Δp 30 bar
HR = Δp 160 bar (rupture strength Δp 250 bar)
- 5 filter element design:**
E = single-end open
- 6 sealing material:**
P = Nitrile (NBR)
V = Viton (FPM)
- 7 filter element specification:**
- = standard
VA = stainless steel
IS06 = for HFC applications, see sheet-no. 31601
- 8 process connection:**
P = manifold mounted
- 9 process connection size:**
4 = DN 20 (HPP 60-150)
5 = DN 22 (HPP 170-450)
- 10 filter housing specification:**
- = standard
IS06 = for HFC applications, see sheet-no. 31605
- 11 internal valve:**
- = without
S1 = with by-pass valve Δp 3,5 bar
S2 = with by-pass valve Δp 7,0 bar
R = reversing valve, $Q \leq 70,06$ l/min (HPP 60-150)
 $Q \leq 211,008$ l/min (HPP 170-450)
- 12 clogging indicator or clogging sensor:**
- = without
AOR = visual, see sheet-no. 1606
AOC = visual, see sheet-no. 1606
AE = visual-electric, see sheet-no. 1615
VS5 = electronic, see sheet-no. 1619

To add an indicator/sensor to your filter, use the corresponding indicator data sheet to find the indicator details and add them to the filter assembly model code.

Filter element: (ordering example)

01E. 90. 10VG. HR. E. P. -

1	2	3	4	5	6	7
---	---	---	---	---	---	---

- 1 series:**
01E. = filter element according to company standard
- 2 nominal size:** 60, 90, 150, 170, 240, 360, 450
- 3 - 7** see type index-complete filter

Technical data:

operating temperature:	-10°C to +100°C
operating medium	mineral oil, other media on request
max. operating pressure:	315 bar
test pressure:	450 bar
process connection:	manifold mounted
housing material:	C-steel
sealing material:	Nitrile (NBR) or Viton (FPM), other materials on request
installation position:	vertical

Classified under the Pressure Equipment Directive 2014/68/EU for mineral oil (fluid group 2), Article 4, Para. 3.
 Classified under ATEX Directive 2014/34/EU according to specific application (see questionnaire sheet-no. 34279-4).

Pressure drop flow curves:

Filter calculation/sizing

The pressure drop of the assembly at a given flow rate Q is the sum of the housing Δp and the element Δp and is calculated as follows:

$$\Delta p_{assembly} = \Delta p_{housing} + \Delta p_{element}$$

$$\Delta p_{housing} = (\text{see } \Delta p = f(Q) \text{ - characteristics})$$

$$\Delta p_{element} (mbar) = Q \left(\frac{l}{min} \right) \times \frac{MSK (mbar)}{10 (l/min)} \times \nu \left(\frac{mm^2}{s} \right) \times \frac{\rho}{0,876} \left(\frac{kg}{dm^3} \right)$$

For ease of calculation our Filter Selection tool is available online at www.eaton.com/hydraulic-filter-evaluation



Material gradient coefficients (MSK) for filter elements

The material gradient coefficients in mbar/(l/min) apply to mineral oil (HLP) with a density of 0,876 kg/dm³ and a kinematic viscosity of 30 mm²/s (139 SUS). The pressure drop changes proportionally to the change in kinematic viscosity and density.


HPP	VG						G		
	1VG	3VG	6VG	10VG	16VG	25VG	25G	40G	80G
60	7,460	5,438	3,775	2,417	2,104	1,438	0,2205	0,1635	0,1526
90	4,487	3,271	2,271	1,454	1,266	0,865	0,1333	0,0988	0,0922
150	2,678	1,952	1,355	0,867	0,755	0,516	0,0796	0,0590	0,0551
170	3,001	2,187	1,518	0,972	0,846	0,578	0,0685	0,0640	0,0438
240	2,312	1,685	1,170	0,749	0,652	0,446	0,0531	0,0496	0,0340
360	1,692	1,233	0,856	0,548	0,477	0,326	0,0388	0,0362	0,0248
450	1,245	0,907	0,630	0,403	0,351	0,240	0,0285	0,0266	0,0182

$\Delta p = f(Q)$ – characteristics according to ISO 3968

The pressure drop characteristics apply to mineral oil (HLP) with a density of 0,876 kg/dm³. The pressure drop changes proportionally to the density.



Symbols:



Spare parts:

item	qty.	designation	dimension and article no.							
			HPP 60	HPP 90	HPP 150	HPP 170	HPP 240	HPP 360	HPP 450	
1	1	filter element	01.E60...	01.E90...	01.E150...	01.E170...	01.E240...	01.E360...	01.E450...	
2	1	O-ring	22 x 3,5		304341 (NBR) 304392 (FPM)	34 x 3,5		304338 (NBR) 304730 (FPM)		
3	1	O-ring	54 x 3		304657 (NBR) 304720 (FPM)	75 x 3		302215 (NBR) 304729 (FPM)		
4	1	support ring	61 x 2,6 x 1			304660	81 x 2,6 x 1			304581
5	2	O-ring	22 x 3		304387 (NBR) 304931 (FPM)	24 x 3		303038 (NBR) 304397 (FPM)		
6	1	clogging indicator, visual				AOR or AOC	see sheet no. 1606			
7	1	clogging indicator, visual-electric				AE	see sheet no. 1615			
8	1	clogging sensor, electronic				VS5	see sheet no. 1619			
9	1	screw plug				20913-4	309817			

item 9 execution only without clogging indicator or clogging sensor

Test methods:

Filter elements are tested according to the following ISO standards:

ISO 2941	Verification of collapse/burst resistance
ISO 2942	Verification of fabrication integrity
ISO 2943	Verification of material compatibility with fluids
ISO 3723	Method for end load test
ISO 3724	Verification of flow fatigue characteristics
ISO 3968	Evaluation of pressure drop versus flow characteristics
ISO 16889	Multi-pass method for evaluating filtration performance

North America
44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Grater China
No. 7, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Europe/Africa/Middle East
Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0

Friedensstraße 41
68804 Altlufheim, Germany
Tel: +49 6205 2094-0

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

Asia-Pacific
100G Pasir Panjang Road
#07-08 Interlocal Centre
Singapore 118523
Tel: +65 6825-1668

**For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration**

© 2021 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.